







APPLETON™ LED LUMINAIRES

by Emerson

Werner Electric Supply has increased our inventory to match your lighting product needs! Our new inventory includes task lighting, mounting hoods, and accessories. For more information, please contact your Werner Electric Supply representative.

Contender™ LED <i>Enclosed and Gasketed</i>	
	Catalog No. VMV5LCD5BU (150W)
	Application: Task
	Lumen Output: 3,000–5,500
	Equivalency: 70W–175W HID
	Wattage: 27W–50W
	Efficacy: 125
	Voltage: 120–277 Vac; 125–300 Vdc 347–480 Vac
CCT/CRI: 5000K/70	
Designed to directly retrofit (no adapter) to Crouse-Hinds™ Champ® VMV Series mounting hoods.	
Hazardous Certifications: NEC/CEC: Class I, Division 2, Groups A, B, C, D; Class II, Division I, Groups E, F, G; Class I, Zone 2.	

Mercmaster™ LED Low Profile <i>Enclosed and Gasketed</i>	
	Catalog No. MLLED3CP5BU (100W) MLLED4CP5BU (150W)
	Application: Task
	Lumen Output: 2,800–5,500
	Equivalency: 70W–175W HID
	Wattage: 27W–50W
	Efficacy: 125
	Voltage: 120–277 Vac; 125–300 Vdc 347–480 Vac
CCT/CRI: 3000K/70, 4000K/70, 5000K/70	
Certified for Ordinary Location and Hazardous Locations.	
Hazardous Certifications: NEC/CEC: Class I, Division 2, Groups A, B, C, D; Class II, Division I, Groups E, F, G; Class I, Zone 2. ATEX/IECEX: Zone 2, 21, 22.	

Mercmaster™ LED Low Profile <i>Enclosed and Gasketed Fixtures & Accessories</i>				
Fixtures & Accessories	Product Description	Hub Size	Catalog No. (NEC/CEC & ATEX/IEC)	
	Pendant Mount	One hub, Rigid Mounting	3/4	KPA-75
	Ceiling Mount	Five Hubs, Four Close-Ups Plugs	3/4	KPC-75
	Wall Mount	Five Hubs, Four Close-Up Plugs	3/4	KPWB-75
	25° Stanchion Mount	One Hub	1-1/4	KPS-125
	Polycarbonate Globe	Diffused Globe	N/A	VPGL-DIFF